

Appln No. 10/693,869
Amdt. Dated April 12, 2005
Response to Office Action of March 10, 2005

3

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An inkjet printer which comprises
a support structure;
an ink reservoir arrangement mounted on the support structure;
an array of printhead chips defining a stationary pagewidth printhead mounted on the
ink reservoir arrangement to receive ink from the ink reservoir arrangement;
an ink transfer roller that is rotatably mounted on the support structure operatively
with respect to the array of printhead chips so that the printhead chips can carry out a
printing operation on the transfer roller as the transfer roller rotates;
a retaining mechanism that is mounted on the support structure to bear against the
ink transfer roller, a sheet of print medium being receivable between the retaining
mechanism and the transfer roller so that ink printed on the transfer roller is transferred to
the sheet of print medium as the transfer roller rotates; and
a feed mechanism mounted on the support structure for feeding the sheet of print
medium between the ink transfer roller and the retaining mechanism.
2. (Original) An inkjet printer as claimed in claim 1, which includes
a housing that defines a receiving formation;
a chassis that is positioned in the housing; and
a media tray assembly that is received in the receiving formation and is displaceably
engageable with the chassis to permit the media tray assembly to be received in, and
withdrawn from, the receiving formation, the media tray assembly and the housing defining
a print medium feed path, the media tray assembly having a media tray in which a stack of
print medium sheets can be stored, the feed mechanism being positioned on the media tray
to feed the sheets from the tray, the support structure being defined by the media tray at a
downstream end of the media tray.
3. (Original) An inkjet printer as claimed in claim 2, in which the ink reservoir
arrangement defines a number of ink reservoirs in which respective inks can be stored.
4. (Original) An inkjet printer as claimed in claim 3, which includes an ink connector
arrangement that is in fluid communication with the ink reservoirs, the ink connector

Appin No. 10/693,869
Amdt. Dated April 12, 2005
Response to Office Action of March 10, 2005

4

arrangement being configured to permit an ink cartridge to be connected to the media tray to supply the reservoirs with ink.

5. (Original) An inkjet printer as claimed in claim 2, in which a power and data supply arrangement for the printhead chip array is positioned on the housing and the housing and media tray assembly include complementary releasable electrical connectors that engage each other when the media tray assembly is received in the receiving formation and disengage each other when the media tray assembly is withdrawn from the receiving formation, the electrical connector of the media tray assembly being connected to the array of printhead chips so that power and data can be supplied to the printhead chips.

6. (Original) An inkjet printer as claimed in claim 5 in which the electrical connectors are in the form of complementary contact moldings.

7. (Original) An inkjet printer as claimed in claim 6, in which a flexible PCB is connected between the contact molding on the media tray assembly and the array of printhead chips.

8. (Currently Amended) An inkjet printer which comprises

a support structure;

a pair of opposed ink reservoir arrangements mounted on the support structure;

an array of printhead chips mounted on each ink reservoir arrangement to receive ink from the ink reservoir arrangement and so as to define a stationary pagewidth printhead on each ink reservoir arrangement;

a pair of ink transfer rollers that is rotatably mounted on the support structure, each ink transfer roller being positioned adjacent one respective array of printhead chips so that the printhead chips can carry out a printing operation on the transfer rollers as the transfer rollers rotate, the transfer rollers being positioned to bear against each other, a sheet of print medium being receivable between the transfer rollers so that ink printed on the transfer rollers is transferred to both sides of the sheet of print medium as the transfer rollers rotate; and

a feed mechanism for feeding the sheet of print medium between the ink transfer rollers.

9. (New) An inkjet printer as claimed in claim 1, wherein:

the array of printhead chips has a sealing arrangement defined thereabout; and

Appln No. 10/693,869
Amdt. Dated April 12, 2005
Response to Office Action of March 10, 2005

5

the ink reservoir arrangement is operatively arranged to, during a printing operation, maintain a spaced relationship of the array of printhead chips and the transfer roller, and, during a non-printing operation, place the array of printhead chips against the transfer roller so that the printhead chips are sealed by the sealing arrangement and transfer roller.